



Robertson Microlit Laboratories

1705 U.S. Highway 46 / Suite 1D / Ledgewood, NJ 07852
(973) 966-6668 / Fax: (973) 966-0136
www.robertson-microlit.com
results@robertson-microlit.com

THERMAL ANALYSIS REQUEST

DATE RECORD

FILE ID

FOR RML USE ONLY

SAMPLE #:

CHARGE TO:

DATE:

REPORT TO:

PO# OR CREDIT CARD INFO:

COMPANY NAME:

PHONE: () -

ADDRESS:

FAX: () -

EMAIL: _____

ALL contact information mandatory

DSC: (3-4 mg sample required)

YES

NO

GMP

Use Default Parameters:

Sealed pan

Heating rate 10°C/min

Temp range 25°C - 350°C

Use Client Parameters:

Type of pan: sealed perforated

Heating rate: _____

Temp Range: _____ °C to _____ °C

(normal range within 0 °C to 600 °C)

Type of transition expected: _____
(if known)

TGA: (3-4 mg sample required)

YES

NO

GMP

Use Default Parameters:

Heating rate 10°C/min

Temp range 25°C - 350°C

Use Client Parameters:

Heating rate: _____

Temp Range: _____ °C to _____ °C

(normal range within 25 °C to 700 °C)

Graphic report options: % weight loss vs. temp.
 other _____

MELTING POINT: YES

NO

Amount of Sample Provided: _____

GMP

FORMAL REPORT GENERATED FOR ALL RESULTS – DATA ARCHIVED ON DISK

CUSTOMER SPECIAL INSTRUCTIONS